


# Alu Plate - Alu Blanket



HD print level



humidity  
resistant



mechanical  
resistance



protection  
ring



solvent  
resistant

Blanket and plate mounting sleeve for use on roto-offset presses with variable format in the printing range 14" -32" especially designed for label and narrow web printing. The products AluSleeve are totally encapsulated in fibreglass and mount a special aluminum tube as external surface for a unique guarantee of repeat conservation and resistance to the chemicals used in offset printing. Moreover the aluminum weight is compensated by the internal structure in material that guarantees an exceptional mechanical strength to the sleeve. The Alu Plate sleeve has a high thickness aluminum tube with the special offset plate holding configuration to allow the installation of the offset plate while the Alu Blanket has a lower thickness tube with an horizontal line as a reference for blanket mounting. The protection steel ring integrates the register notch.

## structure

Fibreglass sleeve with aluminium outer. Made with 2 different intermediate layers, which are ultra-light for manual movement: layers of polyurethane.

## specifications

<b>Colour</b>	Aluminum
<b>Min/Max Printing repeat</b>	14" - 32"
<b>Min/Max Length - Tolerance UNI:ISO 2768T1m</b>	400 - 1.000 [mm] // 15.748" - 39.37"
<b>Register notch</b>	Protection steel ring with integrated register notch
<b>Plate blockage</b>	External notch with blockage manufactured based on OEM specifications
<b>Compressed air for sleeve assembly</b>	6 - 10 [bar] // 87 - 145 PSI Minimum capacity: 700 [l//min] with air input having a free passage with D => 8[mm]
<b>Operating temperature</b>	18° - 40 °C // 64,4 - 104 °F
<b>Working tolerance</b>	External finishing with precision grinding (Ra=0.8) with T.I.R. < 0.015 mm] when measured on a mandrel with T.I.R. <= 0.005 [mm]

Rossini S.p.A. provides no warranties that the contents of this document demonstrate, in particular, the fitness of the products it contains for any specific purpose; we therefore ask customers to verify in advance that the product's characteristics are suitable for its intended use. Rossini S.p.A. reserves the right to update this publication and periodically modify its contents, including technical/commercial information, without further notice of the amendments or changes made. This document and any logos, trademarks and specifications etc. it contains are protected by copyright laws with all rights reserved.



**Rossini World**  
Italy • France • Spain  
Germany • United Kingdom  
Romania • Brasil • China  
United States • India

**Rossini S.p.A. HeadQuarters**  
Via de Gasperi, 5  
20027 Rescaldina - Milano - Italy  
Tel. +39 0331 47 27 11 - Fax +39 0331 57 97 46  
comm.dept@rossini-spa.it

**WWW.ROSSINI-SPA.IT**