

1928

Blanket mounting sleeve for use on roto-offset presses with variable printing (range 14"- 32"). The sleeve is totally encapsulated in fibreglass with an external layer of epoxy resin guaranteeing a perfect dimensional stability over time and excellent chemical resistance against solvents and humidity. Over the external surface is made an horizontal line as a reference for blanket mounting. The protection steel ring integrates the register notch.

## structure

Fibreglass sleeve made with 2 different intermediate layers, which are ultra-light for manual movement. Outer coating in fiberglass.

## specifications

Colour	Yellow (Fibreglass)
Min/Max Printing repeat	14" - 32"
Min/Max Length - Tolerance UNI:ISO 2768T1m	400 - 1000 [mm] // 15.748" - 39.37"
Register notch	Protection steel ring with integrated register notch
Surface hardness - Tolerance +/-5 Shore D	90 Shore D Fibreglass
Compressed air for sleeve assembly	6 - 10 [bar] // 87 - 145 PSI Minimum capacity: 700 [l//min] with air input having a free passage with D => 8[mm]
Operating temperature	18° - 40 °C // 64,4 - 104 °F
Working tolerance	External finishing with precision grinding (Ra=0.8) with T.I.R. < 0.02 [mm] when measured on a mandrel with T.I.R. <= 0.005 [mm]
Cleaning and Storage	Use ethanol with an additional max 20% of ethyl acetate; store vertically

Rossini S.p.A. provides no warranties that the contents of this document demonstrate, in particular, the fitness of the products it contains for any specific purpose; we therefore ask customers to verify in advance that the product's characteristics are suitable for its intended use. Rossini S.p.A. reserves the right to update this publication and periodically modify its contents, including technical/commercial information, without further notice of the amendments or changes made. This document and any logos, trademarks and specifications etc. it contains are protected by copyright laws with all rights reserved.



Rossini World Italy • France • Spain Germany • United Kingdom Romania • Brasil • China United States • India Rossini S.p.A. HeadQuarters Via de Gasperi, 5 20027 Rescaldina - Milano - Italy Tel. +39 0331 47 27 11 - Fax +39 0331 57 97 46 comm.dept@rossini-spa.it