

Special anti-deflection design of the mandrel for using the rubber Speedwell sleeves in heavy-duty applications. The mandrel has the patented tapered value, a close chamber distribution system for the compressed air and moreover the perfect grinding of the surface that can be supplied with chrome, nickel coating according to the manufacturing drawing for the easy and proper mounting of the rubber Speedwell Sleeves.

specifications

Material	Standard: Carbon steel
Conicity	According to patented Rossini Speedwell System standards
Compressed air for mounting sleeve	Pressure: 12-20 [Bar] 174 - 290 [PSI] - Delivery rate: 10 [NI/min]
Applicable load	Up to 40 [Kg/cm] in relation to length and diameter of mandrel
Machining tolerance	High precision ground outer finish (Ra 0.8). Parallelism and coaxiality tolerance < 0.01 [mm]
Surface finishes	Tempered or chrome plated ground mandrel surface treatment; tempered journal bearing contact zones
DIN ISO 1940-1S balance quality grade	Standard G6.3 at 1000 rpm
Available accessories	Tempered bearing guide bushings - 1-way or 2-way rotary joints
	The characteristics of the mandrel or roller supplied are compliant with the drawing and design specifications defined by the manufacturer of the machine.

Rossini S.p.A. provides no warranties that the contents of this document demonstrate, in particular, the fitness of the products it contains for any specific purpose; we therefore ask customers to verify in advance that the product's characteristics are suitable for its intended use. Rossini S.p.A. reserves the right to update this publication and periodically modify its contents, including technical/commercial information, without further notice of the amendments or changes made. This document and any logos, trademarks and specifications etc. it contains are protected by copyright laws with all rights reserved.



Rossini World Italy • France • Spain Germany • United Kingdom Romania • Brasil • China United States • India Rossini S.p.A. HeadQuarters Via de Gasperi, 5 20027 Rescaldina - Milano - Italy Tel. +39 0331 47 27 11 - Fax +39 0331 57 97 46 comm.dept@rossini-spa.it