Thin A







hardness 90 ShD



high longevity



humidity resistant



solvent resistant

Plate mounting sleeve for use with double-sided adhesive cushion tapes. Made of fibreglass for first printing repeat (on a press mandrel and/or Rossini carrier). Furthermore, it can be used for storage of repetitive prints thanks to its competitive price.

structure

Fibreglass base sleeve with milled register notch

specifications

Colour	Yellow
Max Diameter	700 [mm] // 27.559"
Min/Max Length - Tolerance UNI:ISO 2768T1m	350 - 2.850 [mm] // 13.78" - 112.205"
Thickness	0,7 [mm] - 1,9 [mm] // 0.028" - 0.075"
Surface hardness - Tolerance +/-5 Shore D	90 Shore D
Compressed air for sleeve assembly	6 - 10 [bar] // 87 - 145 PSI Minimum capacity: 700 [l//min] with air input having a free passage with D => 8[mm]
Register notch	Milled notch
Standard reference guidelines	1 longitudinal corresponding to the register notch – 1 circumferential in centre
Operating temperature	18° - 40 °C // 64,4 - 104 °F
Working tolerance	External finishing with precision grinding (Ra=0.8) with T.I.R. < 0.02 mm] when measured on a mandrel with T.I.R. <= 0.005 [mm]
Cleaning and Storage	Use ethanol with an additional max 20% of ethyl acetate; store vertically

Rossini S.p.A. provides no warranties that the contents of this document demonstrate, in particular, the fitness of the products it contains for any specific purpose; we therefore ask customers to verify in advance that the product's characteristics are suitable for its intended use. Rossini S.p.A reserves the right to update this publication and periodically modify its contents, including technical/commercial information, without further notice of the amendments or changes made. This document and any logos, trademarks and specifications etc. it contains are protected by copyright laws with all rights reserved.





Rossini World Italy • France • Spain Germany • United Kingdom Romania • Brasil • China

United States • India